

Annual Inspection

To reassure your maintenance is being properly performed we request an annual inspection. It's mandatory for all **Ceramic Pro** coatings according to the **Warranty Guidelines**. We strongly suggest it for all other coatings as well.

The inspection will check over your vehicle and rest assured the protective coating is performing at its best. After review we can advise the best maintenance of your protection for many years to come.

FOR THE BEST PROTECTION!



CERAMIC PRO



FEYNLAB



proceramic.net
bestautosalon.com

PRO CERAMIC - Best Auto Salon

11810 Pika Drive
Waldorf MD 20603
301 557 0035

Info@bestautosalon.com

PROTECTING YOUR
INVESTMENT



PRO CERAMIC



Best Auto Salon
Waldorf, Md

Car Wash

The total curing time is 2 weeks so we highly recommend not washing your vehicle until 2 weeks from delivery. During that time please remove any bird droppings or bug splatters with a damp 365 + GSM microfiber gently as the coating will still be soft.

TIPS

No Rinse or PH neutral mild soap at least bi weekly to avoid dirt build up.

Avoid washing in direct sunlight to prevent water streaking & staining.

Wash your vehicle from top to bottom leaving the most dirty sections LAST including the wheels.

Preferably a "Two bucket method" with dirt trapping filters in the in bottom section.

Use separate soap & sponge/mitt/towels for wheels to prevent cross contamination.

TOUCHLESS Automatic carwashes can be safe to maintain your vehicle as long as its followed up with a clean 365+ GSM microfiber removing droplets.

Foam Cannon Method Initially rinse vehicle with high pressure nozzle or pressure washer. Use a foam cannon gun to saturate vehicle in soap suds. Allow suds to sit 5 -7 minutes. Power wash and rinse your vehicle. **DO NOT ATTEMPT IN DIRECT SUNLIGHT !**

Things to Avoid

Please be mindful that even though our coatings are designed to protect your clearcoat they are not "Bulletproof" and will require basic maintenance to preserve your surface finish at its best.

Lawn Sprinklers - Coating will not protect clearcoat from water spots. Minerals from sprinklers leave water rings on the coating just as it would to your factory clearcoat.

Environmental - Bird droppings, pollen, bugs, and sap from shedding trees

Fleet Trucks - to avoid any possible rock chips or debris

Scrub brush - abrasive soaps, cleaners, or brushes on paint finishes

Brush type carwashes - Do NOT use carwashes with manual or automated brushes. The materials used are too coarse and will breakdown the coatings significantly over a short period of time

If you notice any bird droppings, sap, pollen remove immediately with a damp microfiber 300+ GSM immediately within 2 weeks of cure time as the coating has not reached its maximum hardness.

Drying

Never let any car wash "air" dry otherwise signs of water spotting will appear staining the coating

Highly recommended to use "blow dry" system - power or leaf blower

No Brush Type Carwash



Water Spots

If you ever notice water spots or stains :

DO NOT try to remove them with abrasive polishes or a dry microfiber.

DO NOT attempt use excessive force to remove the blemishes.

DO NOT request a third party detailer or repair shop to remove them.

Contact us immediately for an inspection and we can advise or perform the best remedy.